

規格表 Main specification

床面旋徑	Max swing over bed	Ø350mm
最大加工直徑	Max turning dia	Ø75mm(筒夾式)
最大加工長度	Max turning length	200mm
X軸行程	X axis travel	300mm
Z軸行程	Z axis travel	±250mm
X軸位移速度	X axis max speed	10 m/min
Z軸位移速度	Z axis max speed	20 m/min
主軸型式	Spindle type	雙向通孔
主軸轉速	Spindle speed range	3000rpm
主軸馬達	Spindle drive motor	7.5/5.5 kw
油壓馬達	Hydraulic motor	2HP
冷卻油容量	Coolant tank cap city	120L
體積(長X寬X高)	Volume	3150X2150X1750
機台重量	Weight	4450kg

標準附件

FANUC電腦控制器	FANUC CNC controller	1SET
油壓刀塔 8T X 2	Hydraulic turret	2SET
內徑刀座Ø40 X 8	Boring bar holder	8PCS
外徑刀座□25 X 4	OD tool holder	4PCS
端面刀座□25 X 2	Facing holder	2PCS
銅球Ø10 X 20	Copper ball	20PCS
刀具套筒Ø8~Ø32mmX各2PCS	Sleeve Ø8~Ø32mm	2PCS For Each
警示燈、工作燈	Alarm and working lamp	1PCS
工具、工具箱	Tool and tool box	1SET
鏈板輸送機、除屑車	Chip conveyor and chip bucket	1SET
腳踏開關	Foot switch	1PCS



冠昱機械股份有限公司

Guan-Yu Machinery Co., Ltd.

CNC 雙刀塔車床

KL-400

