



登宇銑床 DENG-YEU MILLING MACHINE

MODEL:2500 CV



規格 MODEL		2500 CV
工作台 TABLE		
工作台面積	Working surface of table	1500x352mm
左右行程	Longitudinal travel	1050mm
前後行程	Cross travel	350mm
上下行程	Vertical travel	390mm
T型槽尺寸	T-slots (size x number x distance)	18mx3x70mm
前後左右進給速率	Range of longitudinal feeds (mm/min)	0-1500mm
前後左右快移速率	Rapid longitudinal traverse (mm/min)	4000mm
上下快移速率	Rapid vertical traverse	125(500)mm
立主軸 VERTICAL SPINDLE		
主軸轉速	Range of spindle speeds (20set tepts)	20段(20set tepts)75-3600 無段(Non-set tep)0-3600
主軸通心軸上下行程	Spindle travel	140m/m
主軸端孔斜度	Taper of spindle nose	NST40#
立銑頭之旋轉角度左右各	Swivelling angle of vertical milling head (R&L) each side	90°
主軸端至工作台面之距離	Distance of spindle end to table top	V:高(MAX)550,低(MIN)160
伸臂前後移動距離	Traverse of over arm	450mm
主軸進給3段	Feed of spindle (3 steps)	無段(Non-set tep)
軸心至機柱擱動之距離	Distance of spindle center to column surface	110mm-700mm
電動機 MOTORS		
立主軸	Vertical spindle	3HP 2/4P (5HP變頻馬達)(Frequency Motor)
工作台前後左右	Table longitudinal feed	AC伺服馬達(Server Motor)
立柱上下	Column up-down	1HP減速馬達(Reducing Motor) AC伺服馬達(Server Motor)
冷卻泵浦	Coolant pump	1/3 HP
淨重	Net weight	2200-2300Kg
包裝尺寸	Packing Measurement (Seaworthy wooden case)	1660x1790x2060mm

※機械規格及設計如有變更,恕不另行通知

※ There will be some changes for the specification and the design from time to time without any prior notice.

標準附件: 1. 冷卻泵浦裝置1式

2. 工具 1 式
3. 工具箱 1 個
4. 銑刀軸 1 式(橫式配件)
5. 銑刀套筒 1 式(橫式配件)

NORMAL ACCESSORIES:

1. One unit of Cooling Pump Device.
2. One unit of Tool.
3. One tool kit.
4. One Milling Knife Axle (horizontal accessory).
5. One Milling Knife Package (horizontal accessory).



登宇機械科技工業有限公司
DENG-YEU MACHINERY TECHNOLOGY CO., LTD.

http://www.dengyeu.com E-mail:service@dengyeu.com
//www.dengyeu.tw service@dengyeu.tw

公 司: 台中市東區振興路364號
通訊處: 台中市南屯區南屯路文山南巷9-1號
No. 9-1 Wen Shan Nan Lane, Nan Gwen Road,
Nan Gwen District Taichung Taiwan R.O.C.
Tel:04-2381-1347 Fax:+886-4-2381-6095