



ISO 9001 認證

鋸切機械專業製造廠

SPECIALIST IN A WIDE ARRAY OF CIRCULAR SAWING MACHINES & CUTTING MACHINES

氣壓型圓鋸機

PNEUMATIC TYPE

CIRCULAR
SAWING MACHINE



營業項目

金屬圓鋸機、鋁材切斷機、管棒倒角機、
鋸片研磨機、帶鋸機、圓鋸片

CIRCULAR SAWING MACHINE, ALUMINUM CUTTING
MACHINE, CHAMFERING MACHINE,
GRINDER, BAND SAW MACHINE and SAW BLADE.

CIRCULAR SAWING MACHINE

圓鋸機



C-275 手動型圓鋸機

MANUAL TYPE
SAWING MACHINE

C-275-1A 氣動型圓鋸機

PNEUMATIC TYPE
SAWING MACHINE

C-275-2A 半自動型圓鋸機

SEMI-AUTOMATIC TYPE
SAWING MACHINE

C-275共通功能

1. 雙向夾鉗，鋸切無毛邊、無粉塵、精度高。
2. 可鋸切角度左90度~0度，右90度~45度。
3. 冷卻系統水箱前置設計方便好整理。
4. 鐵屑集中處理，方便乾淨。

FUNCTION

1. Two-way tongs, without bur when sawing, without powder and dust, with high accuracy.
2. Available sawing angles: Left: 90° degree to 0° degree; right: 90° degrees to 45° degrees.
3. The front setting water box design of the cooling system is convenient and easy to clean up.
4. Iron chippings are treated together, convenient and clean.

適用範圍

- 對於較薄的鐵管、不銹鋼管、鋁管、銅管銅條。
- 適用於門窗業者使用或是樣品開發、管件較輕型之業者。

AVAILABLE RANGE

- Available for thinner iron tubes, stainless steel tubes, aluminum tubes, and copper tubes and copper bars.
- Available for the use or the sample developing of door and window proprietors, and available for proprietors of lighter tubes.

C-275手動夾鉗、進刀特點

- 測量尺寸快速、手動夾鉗、手動進退刀，進刀時可隨管件大小自己隨時掌控進刀給予適當壓力，鋸片壽命高。

C-275 FEATURES OF HAND-OPERATED TONGS AND SAW FEEDING

- Quick measurement of the size, hand-operated tongs, hand-operated saw feeding and withdrawing, you can control the saw feeding at any time and give the appropriate pressure in accordance with the size of a tube when doing the action of saw feeding, the saw blade can be used for a long time.

C-275-1A 自動夾鉗、手動進刀特點

- 除C-275等特點外，另一特點在於自動夾緊功能，當鋸切管件長度量測完成，按下開關，立即夾緊管件，可防止沒夾緊就進刀的危險。

C-275-1A FEATURES OF AUTOMATIC TONGS HAND-OPERATED SAW FEEDING

- Besides the features of C-275, the automatic clamping function is another feature. When finishing measuring a tube's length, you can press down the switch, and the tube will be clamped tight immediately, which is able to avoid the danger of saw feeding without being clamped tightly.

C-275-2A 自動夾鉗、自動進退刀特點

- 此機型用於量多，除C-275-1A等特點外，當鋸片與管件長度調整完成後，按下腳踏開關，立即夾緊進刀節省生產時間。

C-275-2A FEATURES OF AUTOMATIC TONGS HAND-OPERATED SAW FEEDING AND WITHDRAWING


- The model is most appropriate for huge amount. When finishing adjusting the saw blade and a tube's length, you can press down the pedal switch, and it will execute the functions of clamping and saw feeding, which will save the production time.

C-275-3A 自動夾鉗、自動進退刀特點

1. 使用PLC控制器，操作集中簡易，靈敏，維修簡便。
2. 浮動送料系統，送料精確快速、不傷工件表面。
3. 裝有數字顯示器，鋸切長度調整容易，快速又精確。
4. 夾鉗壓力可無段調整，確保管件不夾傷變形。
5. 裝有電子式鋸片保護裝置，鋸片磨鈍自動停機。
6. 裝置技術量表可設定數量及停機功能。
7. 無料自動停機裝置。
8. 鐵屑集中裝置，方便乾淨。

C-275-3A FEATURE OF AUTOMATIC TONGS, AUTOMATIC SAW FEEDING AND WITHDRAWING, FEED, AND POSITIONING

1. Using the PLC controller, control buttons are located together, allowing for simple operation, agile, easy to maintain.
2. Uniquely designed, most suited for floating feed system, accurate and rapid feeding does not damage workpiece surfaces.
3. Equipped with digital display for easy cutting length adjustment, quick and accurate.
4. The tong's pressure is adjustable at will, ensuring that the tubes will not deform and be damaged.
5. Equipped with electronic-type saw blade protection device, the machine will stop automatically after the saw blade is blunt.
6. Equipped with the counting device that can set the amount and the function of machine stopping.
7. The automatic non-material machine stopping device.
8. Iron chippings are treated together, convenient and clean.



C-275-3A 自動氣壓型圓鋸機
AIR AUTOMATIC TYPE
SAWING MACHINE



C-300-2A

自動氣壓型圓鋸機
AIR AUTOMATIC TYPE
SAWING MACHINE
強力齒箱，振動鋸切快速。



C-275M 手動型圓鋸機
MANUAL TYPE
SAWING MACHINE

※ 手輪可左右調整角度，速度快且省力。
Control is by hand wheel. The cutting angle can be micro-adjusted.
Adjustment is easy and fast.



型號 Model		C-275	C-275M	C-275-1A	C-275-2A	C-300-2A	C-275-3A
頭部迴轉角度 Head rotation angle		90°	45°	90°	45°	90°	45°
鋸切能力 面積 Sawing Capacity Area: mm	實心棒 Solid bar ●	38	30	38	30	38	30
	圓管 Round tube ○	85	75	85	75	85	75
	角型 Angle steel L	75 x 75	50 x 50	75 x 75	50 x 50	75 x 75	50 x 50
	四方管 Square tube □	75 x 75	75 x 75	75 x 75	75 x 75	75 x 75	75 x 75
	槽型 Trough-shaped steel U	75 x 75	50 x 50	75 x 75	50 x 50	75 x 75	50 x 50
長方型 Rectangular steel ▭	75 x 90	75 x 60	75 x 90	75 x 60	75 x 90	75 x 60	
主機馬達 Cutting Motor		A: 2HP /1.5HP 2P/4P, B: 1.5HP/1HP 4P/8P					
主軸轉速 Cutting Speed		A: 120/60 rpm, B: 60/30rpm					
冷卻水泵 Cooling Pump Power		1/8HP					
使用壓縮空氣 Required air pressure		4-6kgs/cm ²					
適用鋸片 Used Circular Saw Blade		高速鋼鋸外徑 HSS BLADE 250-300mm					
送料長度 Feeding length		3A才有一次送料, 3-700mm, 可三次送料, 最長2100mm 3-700mm(standard) but can be prolonged 2100mm and also can be feed 3 times (just for 3A models)					
機器尺寸 Dimensions (mm)		L710 x W610 x H1350	L850 x W610 x H1350	L850 x W610 x H1350	L850 x W610 x H1350	L1000 x W2150 x H1700	
機器重量 Machine Weight		180kgs	190kgs	240kgs	240kgs	660kgs	
標準附件 Standard Attachments		高速鋼鋸片φ250mm, 一片, 擋尺一支(3A無附), 切削油一瓶, 工具一組, 夾具一組 Standard Accessories: A high-speed steel saw blade, a ruler (not applicable for 3A), a bottle of cutting oil, a set of tools, and a set of clamping apparatus.					

本公司享有規格變更之權利，恕不另行通知。

All Specification, dimensions and design characteristics shown in this catalogue are subject to change without notice.

CIRCULAR SAWING MACHINE

圓鋸機



C-325 手動型圓鋸機
MANUAL TYPE
SAWING MACHINE

C-325-1A 氣動型圓鋸機
PNEUMATIC TYPE
SAWING MACHINE

C-325-2A 半自動型圓鋸機
SEMI-AUTOMATIC TYPE
SAWING MACHINE

C-325系列共通功能

FUNCTION

- | | |
|--|---|
| <ol style="list-style-type: none"> 1. 雙向夾鉗，鋸切無毛邊、無粉塵、精度高。 2. 可鋸切角度左90度~0度，右90度~45度。 3. 冷卻系統水箱前置，設計方便好整理。 4. 鐵屑集中處理，方便乾淨。 | <ol style="list-style-type: none"> 1. Two-way tongs, without bur when sawing, without powder and dust, with high accuracy. 2. Available sawing angles: Left: 90° degrees to 0° degree; right: 90° degrees to 45° degrees. 3. The front setting water box design of the cooling system is convenient and easy to clean up. 4. Iron chippings are treated together, convenient and clean. |
|--|---|

C-325適用範圍

AVAILABLE RANGE

- | | |
|---|--|
| <ul style="list-style-type: none"> ■ 對於厚、中、薄管、實心是一部非常適當的機種由兩組齒輪帶動，扭力大適合較重型鋸切，對於傢俱業、運動器材、鈹金廠、機械廠都很適用。 | <ul style="list-style-type: none"> ■ It is an appropriate machine model for thick, middle, and thin hollow tubes, and solid tubes. This model is driven by two-set gears, with great torque force, suitable for heavy-duty cutting, available for the furniture industry, sports equipment, sheet metal factories, and machine factories. |
|---|--|

C-325手動夾鉗、進刀特點

C-325 FEATURES OF HAND-OPERATED TONGS AND SAW FEEDING

- | | |
|--|---|
| <ul style="list-style-type: none"> ■ 測量尺寸快速、手動夾鉗、手動進退刀，進刀時可隨管件大小自己隨時掌控進刀給予適當壓力，鋸片壽命高。 | <ul style="list-style-type: none"> ■ Quick measurement of the size, hand-operated tongs, hand-operated saw feeding and withdrawing; you can control the saw feeding at any time and give the appropriate pressure in accordance with the size of a tube when doing the action of saw feeding; the saw blade can be used for a long time. |
|--|---|

C-325-1A 自動夾鉗、手動進刀特點

C-325-1A FEATURES OF AUTOMATIC TONGS HAND-OPERATED SAW FEEDING

- | | |
|--|---|
| <ul style="list-style-type: none"> ■ 除C-325等特點外，另一特點在於自動夾緊功能，當鋸切管件長度量測完成，按下開關，立即夾緊管件，可防止沒夾緊就進刀的危險 | <ul style="list-style-type: none"> ■ Besides the features of C-325, the automatic clamping function is another feature. When finishing measuring a tube's length, you can press down the switch, and the tube will be clamped tight immediately, which is able to avoid the danger of saw feeding without being clamped tightly. |
|--|---|

C-325-2A 自動夾鉗、自動進退刀特點


C-325-2A FEATURES OF AUTOMATIC TONGS AUTOMATIC SAW FEEDING AND WITHDRAWING

- | | |
|--|---|
| <ul style="list-style-type: none"> ■ 此機型用於量多，除C-325-1A等特點外，當鋸片與管件長度調整完成後，按下腳踏開關，立即夾緊進刀節省生產時間。 | <ul style="list-style-type: none"> ■ The model is most appropriate for huge amount. When finishing adjusting the saw blade and a tube's length, you can press down the pedal switch, and it will execute the functions of clamping and saw feeding, which will save the production time. |
|--|---|

C-325-3A 自動夾鉗、進退刀、送料、定寸特點

C-325-3A FEATURE OF AUTOMATIC TONGS, AUTOMATIC SAW FEEDING AND WITHDRAWING, FEED AND POSITIONING

- | | |
|---|---|
| <ol style="list-style-type: none"> 1. 使用PLC控制器，操作集中簡易，靈敏，維修簡便。 2. 浮動送料系統，送料精確快速、不傷工件表面。 3. 裝有數字顯示器，鋸切長度調整容易，快速又精確。 4. 夾鉗壓力可無段調整，確保管件不夾傷變形。 5. 裝有電子式鋸片保護裝置，鋸片磨鈍自動停機。 6. 裝置技術量表可設定數量及停機功能。 7. 無料自動停機裝置。 8. 鐵屑集中裝置，方便乾淨。 | <ol style="list-style-type: none"> 1. Using the PLC controller, control buttons are located together, allowing for simple operation, agile, easy to maintain. 2. Uniquely designed, most suited for floating feed system, accurate and rapid feeding does not damage workpiece surfaces. 3. Equipped with digital display for easy cutting length adjustment, quick and accurate. 4. The tong's pressure is adjustable at will, ensuring that the tubes will not deform and be damaged. 5. Equipped with electronic-type saw blade protection device, the machine will stop automatically after the saw blade is blunt. 6. Equipped with the counting device that can set the amount and the function of machine stopping. 7. The automatic non-material machine stopping device. 8. Iron chippings are treated together, convenient and clean. |
|---|---|



C-325-3A

自動氣壓型圓鋸機

AIR AUTOMATIC TYPE
SAWING MACHINE

※半護罩為選購配備
Optional attachments
of half protect cover



型號 Model		C-325		C-325-1A		C-325-2A		C-325-3A
頭部迴轉角度 Head rotation angle		90°	45°	90°	45°	90°	45°	90°
鋸切能力 面積	實心棒 Solid bar ●	55	45	55	45	55	45	55
	圓管 Round tube ○	105	100	105	100	105	100	105
Sawing Capacity Area: mm	角型 Angle steel L	100 x 100	90 x 90	100 x 100	90 x 90	100 x 100	90 x 90	100 x 100
	四方管 Square tube □	100 x 100	90 x 90	100 x 100	90 x 90	100 x 100	90 x 90	100 x 100
	槽型 Trough-shaped steel U	100 x 100	90 x 90	100 x 100	90 x 90	100 x 100	90 x 90	100 x 100
	長方型 Rectangular steel □	125 x 90	125 x 80	125 x 90	125 x 80	125 x 90	125 x 80	125 x 90
主機馬達 Cutting Motor		A: 3HP/2HP 2P/4P, B: 2HP/1.5HP 4P/8P						
主軸轉速 Cutting Speed		A: 100/50 rpm B: 50/25 rpm						
冷卻水泵 Cooling Pump Power		1/8HP						
使用壓縮空氣 Required air pressure		4-6kgs/cm ²						
適用鋸片 Used Circular Saw Blade		高速鋼鋸外徑 HSS BLADE 250-325mm						
送料長度 Feeding length		3A才有一次送料, 3-700mm, 可三次送料, 最長2100mm 3-700mm(standard) but can be prolonged 2100mm and also can be feed 3 times (just for 3A models)						
機器尺寸 Dimensions (mm)		L1000 x W650 x H1420	L1000 x W650 x H1420	L1000 x W850 x H1350	L1000 x W2150 x H1700			
機器重量 Machine Weight		240kgs	250kgs	300kgs	700kgs			
標準附件 Standard Attachments		高速鋼鋸片 HSS Blade ø300mm, 擋尺一支(3A無附), 切削油一瓶, 工具一組, 夾具一組 Standard Accessories: A high-speed steel saw blade, a ruler (not applicable for 3A), a bottle of cutting oil, a set of tools, and a set of clamping apparatus.						

本公司享有規格變更之權利，恕不另行通知。

All Specification, dimensions and design characteristics shown in this catalogue are subject to change without notice.

CIRCULAR SAWING MACHINE

圓鋸機



C-370 手動型圓鋸機
MANUAL TYPE
SAWING MACHINE

C-370-1A 氣動型圓鋸機
PNEUMATIC TYPE
SAWING MACHINE

C-370-2A 半自動型圓鋸機
SEMI-AUTOMATIC TYPE
SAWING MACHINE

C-370系列共通功能

FUNCTION

1. 雙向夾鉗，鋸切無毛邊、無粉塵、精度高。
2. 可鋸切角度左90度~0度，右90度~45度。
3. 冷卻系統水箱前置設計方便好整理。
4. 鐵屑集中處理，方便乾淨。

1. Two-way tongs, without bur when sawing, without powder and dust, with high accuracy.
2. Available sawing angles: Left: 90° degrees to 0° degree; right: 90° degrees to 45° degrees.
3. The front setting water box design of the cooling system is convenient and easy to clean up.
4. Iron chippings are treated together, convenient and clean.

C-370適用範圍

AVAILABLE RANGE

- 對於厚、中、薄管、實心是一部非常適當的機種由兩組齒輪帶動，扭力大適合較重型鋸切，管徑最大可達120mm，方管可達100x100mm，對於傢俱業、運動器材、板金廠、機械廠都很適用。

- It is an appropriate machine model for thick, middle, and thin hollow tubes, and solid tubes. This model is driven by two-set gears, with great torque force, suitable for heavy-duty cutting. The largest pipe diameter can reach 1200, and the square pipe can achieve 100x100mm. It is available for the furniture industry, sports equipment, sheet metal factories, and machine factories.

C-370手動夾鉗、進刀特點

C-370 FEATURES OF HAND-OPERATED TONGS AND SAW FEEDING

- 測量尺寸快速、手動夾鉗、手動進退刀，進刀時可隨管件大小自己隨時掌控進刀給予適當壓力，鋸片壽命高。

- Quick measurement of the size, hand-operated tongs, hand-operated saw feeding and withdrawing; you can control the saw feeding at any time and give the appropriate pressure in accordance with the size of a tube when doing the action of saw feeding; the saw blade can be used for a long time.

C-370-1A 自動夾鉗、手動進刀特點

C-370-1A FEATURES OF AUTOMATIC TONGS HAND-OPERATED SAW FEEDING

- 除C-370等特點外，另一特點在於自動夾緊功能，當鋸切管件長度量測完成，按下開關，立即夾緊管件，可防止沒夾緊進刀的危險。

- Besides the features of C-370, the automatic clamping function is another feature. When finishing measuring a tube's length, you can press down the switch, and the tube will be clamped tight immediately, which is able to avoid the danger of saw feeding without being clamped tightly.

C-370-2A 自動夾鉗、自動進退刀特點

C-370-2A FEATURES OF AUTOMATIC TONGS AUTOMATIC SAW FEEDING AND WITHDRAWING

- 此機型用於量多，除C-370-1A等特點外，當鋸片與管件長度調整完成後，按下腳踏開關，立即夾緊進刀節省生產時間。


- The model is most appropriate for huge amount. When finishing adjusting the saw blade and a tube's length, you can press down the pedal switch, and it will execute the functions of clamping and saw feeding, which will save the production time.

C-370-3A 自動夾鉗、進退刀、送料、定寸特點

C-370-3A FEATURE OF AUTOMATIC TONGS, AUTOMATIC SAW FEEDING AND WITHDRAWING, FEED, AND POSITIONING


1. 使用PLC控制器，操作集中簡易，靈敏，維修簡便。
2. 浮動送料系統，送料精確快速、不傷工件表面。
3. 裝有數字顯示器，鋸切長度調整容易，快速又精確。
4. 夾鉗壓力可無段調整，確保管件不夾傷變形。
5. 裝有電子式鋸片保護裝置，鋸片磨鈍自動停機。
6. 裝置技術量表可設定數量及停機功能。
7. 無料自動停機裝置。
8. 鐵屑集中裝置，方便乾淨。

1. Using the PLC controller, control buttons are located together, allowing for simple operation, agile, easy to maintain.
2. Uniquely designed, most suited for floating feed system, accurate and rapid feeding does not damage workpiece surfaces.
3. Equipped with digital display for easy cutting length adjustment, quick and accurate.
4. The tong's pressure is adjustable at will, ensuring that the tubes will not deform and be damaged.
5. Equipped with electronic-type saw blade protection device, the machine will stop automatically after the saw blade is blunt.
6. Equipped with the counting device that can set the amount and the function of machine stopping.
7. The automatic non-material machine stopping device.
8. Iron chippings are treated together, convenient and clean.



特殊配件 Optional Accessories

1. 變頻器(鋸片轉速改變)
Frequency converter
(For change rpm of saw blade)
2. 氣壓定位檔尺(取料方便快速)
Position ruler with pneumatic
(Take away material
convenient and quick)



C-370-3A 自動氣壓型圓鋸機

AIR AUTOMATIC TYPE
SAWING MACHINE



CM-370 圓鋸機

SAWING MACHINE

型號 Model		C-370	CM-370	C-370-1A	C-370-2A	C-370-3A
頭部迴轉角度 Head rotation angle		90°	45°	左(left)45° · 右(right)45°	90°	45°
鋸切能力 面積 Sawing Capacity Area: mm	實心棒 Solid bar ●	75	70	80	75	70
	圓管 Round tube ○	120	110	115	120	110
	角型 Angle steel L	115 x 115	100 x 100	115 x 115	115 x 115	100 x 100
	四方管 Square tube □	115 x 115	100 x 100	105 x 105	115 x 115	100 x 100
	槽型 Trough-shaped steel U	115 x 115	100 x 100	150 x 75	115 x 115	100 x 100
長方型 Rectangular steel ▭	125 x 100	125 x 100	150 x 50	125 x 100	125 x 100	
主機馬達 Cutting Motor		A: 3HP/2HP - 2/4P, B: 2HP/1.5HP - 4/8P, C: 3HP / 2HP 2/4P				
主軸轉速 Cutting Speed		A: 58/29 rpm, B: 29/15 rpm, C: 50/100 rpm				
冷卻水泵 Cooling Pump Power		1/8HP				
使用壓縮空氣 Required air pressure		4-6kgs/cm ²				
適用鋸片 Used Circular Saw Blade		高速鋼鋸外徑 HSS BLADE 275-370mm				
送料長度 Feeding length		3A才有一次送料, 3-700mm, 可三次送料, 最長2100mm 3-700mm(standard) but can be prolonged 2100mm and also can be feed 3 times (just for 3A models)				
機器尺寸 Dimensions (mm)		L1000 x W650 x H1420	L700 x W970 x H1650	L1000 x W650 x H1420	L1000 x W850 x H1350	L1000 x W2150 x H1700
機器重量 Machine Weight		280kgs	300kgs	290kgs	350kgs	720kgs
標準附件 Standard Attachments		高速鋼鋸片HSS Blade ø300mm, 擋尺一支(3A無附), 切削油一瓶, 工具一組, 夾具一組 Standard Accessories: A high-speed steel saw blade, a ruler (not applicable for 3A), a bottle of cutting oil, a set of tools, and a set of clamping apparatus.				

本公司享有規格變更之權利，恕不另行通知。

All Specification, dimensions and design characteristics shown in this catalogue are subject to change without notice.

毛邊除屑機 BUR CLEAN MACHINE

C-100-SB



型號 Model	C-100-SB	
工件尺寸 Size Of Workpiece	3~100 mm	
主機馬力 Cutting Motor	3HP	
鋼刷輪 Steel Brush Wheel	Dia. 200mm, inner dia.25.4mm	
轉速 Speed	1750 rpm	
使用壓力 Air Pressure	5~6 kg/cm ²	
機械尺寸 Machine Dimensions	L1650 x W750 x H1420mm	
機械重量 Machine Weight	450 kgs	

特點 FEATURES

- 360度銑面銑角，能把鋸切完成鋒利之角屑清除，方便後續加工組裝。
- 使用一般鋼刷輪或帶砂布之研磨輪，成本低，效益高。
- 用度廣，能銑圓管、四方管、四方型、實心棒、鐵板或不規則之鋁擠型、銅及不鏽鋼等材質。
- 360 degree milling face and milling angle, it can clean the bur after cutting.
- Use the grinding wheel of common steel brush wheel, low cost and high benefit.
- Using wide, can milling round tube, solid pipe, square tube, iron plate or irregular aluminum squeeze type, copper and stainless steel, etc.

圓鋸機 SAWING MACHINE

C-325-4A



型號 Model	C-325-4A	
馬達動力 Motor	主馬達 Main Motor	A 3HP/2HP, 2P/4P, B 2HP/1.5HP, 4/8P
	送料馬達 Feed Motor	A100/50, B50/25
夾鉗最大限 Max. Clamping Capacity	110 mm	
鋸片 Max. Saw Blade	250~300 mm	
鋸片孔 Saw Blade Hole	內孔BOREø32mm, 梢孔HOLE11x63x2mm	
最大加工能力 Max. Cutting capacity	●	直徑DIA.40mm, 連續使用直徑Continuous working 40 mm
	□	對邊80mm
	○	直徑DIA. 80mm
最小送料外徑 Min. Outer diameter for feed	15mm	
重量 Net. Weight	450kgs	
送料速度 Max. feed speed	更換皮帶輪大小, 最大可達每分鐘20公尺 Change Pulley	
加工長度 Working length	可依使用需要製作 As Required	

特點 FEATURES

- 自動送料、自動鉗夾、自動鋸切、自動整料。
- 強力齒輪驅動, 適合重切削, 更可增加使用壽命。
- 無毛邊, 無粉塵, 無殘料一人可同時操作數機, 節省人工成本。
- 雙速馬達, 適合銅、鋁、鐵材、鋼料、不鏽鋼材等管類、棒類工作物之自動鋸切。
- 可加裝自動料架, 達到全自動化之目的。
- Auto feed-clamping-cutting & removal
- Powerful gear drive, suitable for heavy cutting, trouble free long term operation.
- Smooth cut face, no waste material, minimum supervision required leaving operator free for additional functions.
- High performance 2 speed motor, auto cutting for tubes or bars of copper, aluminium, iron, stainless steel, ETC.
- Bar feeder can be fitted to the machine for auto operation.